

COMPUTER SCIENCE 88

April 28, 2021

1 Introduction

In Python, we wrote programs using **imperative programming** – a programming style where code is written as a set of instructions for the computer. In contrast, with **declarative programming** our code declares *what* result we want, not *how* to compute it.

SQL is an example of a declarative programming language. Statements do not describe computations directly, but instead describe the desired result of some computation. It is the role of the query interpreter of the database system to plan and perform a computational process to produce such a result.

In SQL, data is organized into *tables*. A table has a fixed number of named columns. A row of the table represents a single data record and has one value for each column. For example, we have a table named `records` that stores information about the employees at a small company¹. The table has five columns, and each of the nine rows represents an employee.

Name	Division	Title	Salary	Supervisor
Ben Bitdiddle	Computer	Wizard	60000	Oliver Warbucks
Alyssa P Hacker	Computer	Programmer	40000	Ben Bitdiddle
Cy D Fect	Computer	Programmer	35000	Ben Bitdiddle
Lem E Tweakit	Computer	Technician	25000	Ben Bitdiddle
Louis Reasoner	Computer	Programmer Trainee	30000	Alyssa P Hacker
Oliver Warbucks	Administration	Big Wheel	150000	Oliver Warbucks
DeWitt Aull	Administration	Secretary	25000	Oliver Warbucks
Eben Scrooge	Accounting	Chief Accountant	75000	Oliver Warbucks
Robert Cratchet	Accounting	Scrivener	18000	Eben Scrooge

¹Example adapted from Structure and Interpretation of Computer Programs

2 Creating Tables

We can use a `select` statement to create tables. The following statement creates a table with a single row, with columns named “first” and “last”:

```
sqlite> select "Ben" as first, "Bitdiddle" as last;  
Ben|Bitdiddle
```

Given two tables with the same number of columns, we can combine their rows into a larger table with `union`:

```
sqlite> select "Ben" as first, "Bitdiddle" as last union  
...> select "Louis",          "Reasoner";  
Ben|Bitdiddle  
Louis|Reasoner
```

To save a table for use later, use `create table` and the name we want to give the table. Here we’re going to create the table of employees from the previous section and assign it to the name `records`:

```
sqlite> create table records as  
...> select "Ben Bitdiddle" as name, "Computer" as division,  
...>    "Wizard" as title, 60000 as salary,  
...>    "Oliver Warbucks" as supervisor union  
...> select "Alyssa P Hacker", "Computer",  
...>    "Programmer", 40000, "Ben Bitdiddle" union ... ;
```

We can select rows from an existing table using a `from` clause. This query creates a table with two columns, with a row for each row in the `records` table:

```
sqlite> select name, division from records;  
Alyssa P Hacker|Computer  
Ben Bitdiddle|Computer  
Cy D Fect|Computer  
DeWitt Aull|Administration  
Eben Scrooge|Accounting  
Lem E Tweakit|Computer  
Louis Reasoner|Computer  
Oliver Warbucks|Administration  
Robert Cratchet|Accounting
```

The special syntax `select *` will select all columns from a table. It's any easy way to print the contents of a table.

```
sqlite> select * from records;
Alyssa P Hacker|Computer|Programmer|40000|Ben Bitdiddle
Ben Bitdiddle|Computer|Wizard|60000|Oliver Warbucks
Cy D Fect|Computer|Programmer|35000|Ben Bitdiddle
DeWitt Aull|Administration|Secretary|25000|Oliver Warbucks
Eben Scrooge|Accounting|Chief Accountant|75000|Oliver Warbucks
Lem E Tweakit|Computer|Technician|25000|Ben Bitdiddle
Louis Reasoner|Computer|Programmer Trainee|30000|Alyssa P Hacker
Oliver Warbucks|Administration|Big Wheel|150000|Oliver Warbucks
Robert Cratchet|Accounting|Scrivener|18000|Eben Scrooge
```

We can choose which columns to show, we can filter out rows using a `where` clause, and sort the resulting rows with an `order by` clause. In general the syntax is

```
select [columns] from [tables]
      where [condition] order by [criteria]
```

For instance, the following statement lists all information about employees with the “Programmer” title.

```
sqlite> select * from records where title = "Programmer";
Alyssa P Hacker|Computer|Programmer|40000|Ben Bitdiddle
Cy D Fect|Computer|Programmer|35000|Ben Bitdiddle
```

The following statement lists the names and salaries of each employee under the accounting division, sorted in descending order by their salaries.

```
sqlite> select name, salary from records
...> where division = "Accounting" order by -salary;
Eben Scrooge|75000
Robert Cratchet|18000
```

2.1 Questions

1. Write a query that outputs the names of employees that Oliver Warbucks directly supervises.

a from clause using the keyword `as` and to refer to a column within a particular table using a dot expression. In the example below we find the name and title of Louis Reasoner's supervisor.

```
sqlite> select b.name, b.title from records as a, records as b
...>   where a.name = "Louis Reasoner" and
...>           a.supervisor = b.name;
Alyssa P Hacker|Programmer
```

3.1 Questions

1. Write a query that creates a table with columns: `employee`, `salary`, `supervisor` and `supervisor's salary`, containing all supervisors who earn more than twice as much as the employee.
2. Write a query that outputs the names of employees whose supervisor is in a different division.
3. Write a query that outputs the meeting days and times of all employees directly supervised by Oliver Warbucks.

3.2 Extra Questions

1. A middle manager is a person who is both supervising someone and is supervised by someone different. Write a query that outputs the names of all middle managers.
2. What is the output of the query in the previous part? Explain the output you get.

3. Write a query that results in the names of all employees that have a meeting on the same day as their supervisor.

4 Aggregation

So far, we have joined and manipulated individual rows using `select` statements. But we can also perform aggregation operations over multiple rows with the same `select` statements.

We can use the `max`, `min`, `count`, and `sum` functions to retrieve more information from our initial tables.

If we wanted to find the name and salary of the employee who makes the most money, we might say

```
sqlite> select name, max(salary) from records;
Oliver Warbucks|150000
```

Using the special `count (*)` syntax, we can count the number of rows in our table to see the number of employees at the company.

```
sqlite> select count(*) from records;
9
```

These commands can be performed on specific sets of rows in our table by using the `group by [column name]` clause. This clause takes all of the rows that have the same value in `column name` and groups them together.

We can find the minimum salary earned in each division of the company.

```
sqlite> select division, min(salary) from records
...> group by division;
Computer|25000
Administration|25000
Accounting|18000
```

